

V-TAC
Meaningful Innovation.

SAMSUNG LED Illuminated

LED Floodlights

V-TAC's LED floodlights are manufactured with industry-leading components to deliver exceptional performance, making them the perfect choice for efficient outdoor lighting. Each unit is designed and made of die-cast aluminium for extreme durability. With the IP65 rating, all the floodlights in this series are also water and dust proof.

This extensive range of floodlights is ready to impress in terms of efficiency brought on by the Samsung LEDs. The PIR series comes with an auto-cutoff function(Manual Override)

Key Features

· 10w to 1000w
· IP65 rating — high-quality components to ensure waterproof/airtight performance
· Modern and strong Die cast aluminium body with a minimalistic design, for high-end support and design
· Product category include high lumen, slimline, PIR series, rechargeable, work floodlight, and sports floodlights
· Select units include a 1 meter wire for easy and convenient installation






IP65 RATING

05 YEAR WARRANTY

135 LUMEN/W

HIGH LUMEN SLIMLINE SERIES

- IP65 Rating.
- SMD-Samsung Chip
- 5 Years Warranty
- AC:220-240V,50Hz
- Body Type: Aluminium
- 115° Beam Angle
- CRI >70
- PF >0.9
- 25,000 hr lifespan
- 0-100% in <1sec

SKU	Model	Watts	Lumens	Box Qty	Diagram	Size
8844 | 4000K DAY WHITE 8845 | 6500K WHITE	VT-4455	50W	5740	10 pcs		183.5x34x169mm
8846 | 4000K DAY WHITE 8847 | 6500K WHITE	VT-44101	100W	11480	4 pcs		253.5x40x242.5mm
8848 | 4000K DAY WHITE 8849 | 6500K WHITE	VT-44201	200W	22960	2 pcs		402.5x44x349.5mm

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.



IP65 RATING







05 YEAR WARRANTY

135 LUMEN/W

1 METER WIRE

HIGH LUMEN SLIMLINE SERIES- 1M WIRE

- IP65 Rating.
- SMD-Samsung Chip
- 5 Years Warranty
- AC:220-240V,50Hz
- Body Type: Aluminium
- 115° Beam Angle
- CRI >70
- PF >0.9
- 25,000 hr lifespan
- 0-100% in <1sec

SKU	Model	Watts	Lumens	Box Qty	Diagram	Size
23196 | 3000K WARM WHITE 23197 | 4000K DAY WHITE 23198 | 6500K WHITE	VT-44033-1	30W	3450	20 pcs		164.5x34x153mm
23199 | 3000K WARM WHITE 23216 | 4000K DAY WHITE 23217 | 6500K WHITE	VT-4455-1	50W	5740	10 pcs		183.5x34x169mm
23200 | 3000K WARM WHITE 23218 | 4000K DAY WHITE 23219 | 6500K WHITE	VT-44101-1	100W	11480	4 pcs		242.5x40x253.5mm
23201 | 4000K DAY WHITE 23202 | 6500K WHITE	VT-44153-1	150W	17220	4 pcs		328.5x43x295mm
23220 | 4000K DAY WHITE 23221 | 6500K WHITE	VT-44201-1	200W	22960	2 pcs		402.5x44x349.5mm
10367 | 4000K DAY WHITE 23203 | 6500K WHITE	VT-44003-1	300W	34440	2 pcs		496x49x445mm

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

NEW







IP65 RATING

05 YEAR WARRANTY

1 METER WIRE

LED FLOODLIGHTS BLACK BODY GREY GLASS

- IP65 Rating
- SMD-Samsung Chip
- 5 Years Warranty
- AC:220-240V,50Hz
- Body Type: Aluminium
- 115° Beam Angle
- CRI >70
- PF >0.9
- 25,000 hr lifespan
- 0-100% in <1sec

SKU	Model	Watts	Lumens	Box Qty	Diagram	Size
23599 | 3000K WARM WHITE	VT-44035-B	30W	2505	10 pcs		164.5x34x153mm
23600 | 6500K WHITE	VT-44055-B	50W	4270	10 pcs		183.5x34x169mm
23440 | 4000K DAY WHITE 23441 | 6500K WHITE	VT-44104-B	100W	8700	4 pcs		253.5x40x242.5mm
23601 | 4000K DAY WHITE 23444 | 6500K WHITE	VT-44204-B	200W	17540	2 pcs		402.5x44x349.5mm

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

NEW





IP65 RATING

05 YEAR WARRANTY

1 METER WIRE

LED FLOODLIGHTS WHITE BODY GREY GLASS

- IP65 Rating
- SMD-Samsung Chip
- 5 Years Warranty
- AC:220-240V,50Hz
- Body Type: Aluminium
- 115° Beam Angle
- CRI >70
- PF >0.9
- 25,000 hr lifespan
- 0-100% in <1sec

SKU	Model	Watts	Lumens	Box Qty	Diagram	Size
23442 | 4000K DAY WHITE 23443 | 6500K WHITE	VT-44104-W	100W	8700	4 pcs		253.5x40x242.5mm
23602 | 4000K DAY WHITE 23603 | 6500K WHITE	VT-44204-W	200W	17540	2 pcs		402.5x44x349.5mm

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.








IP65 RATING

05 YEAR WARRANTY

LED FLOODLIGHTS BLACK BODY GREY GLASS

- IP65 Rating.
- SMD-Samsung Chip
- 5 Years Warranty
- AC:220-240V,50Hz
- Body Type: Aluminium
- 115° Beam Angle
- CRI >70
- PF >0.9
- 25,000 hr lifespan
- 0-100% in <1sec

SKU	Model	Watts	Lumens	Box Qty	Diagram	Size
9898 | 3000K WARM WHITE 9899 | 4000K DAY WHITE 10010 | 6500K WHITE	VT-44010-B	10W	735	40 pcs		104x21x92mm
10014 | 3000K WARM WHITE 10015 | 4000K DAY WHITE 10016 | 6500K WHITE	VT-44020-B	20W	1620	20 pcs		126.5x28x114mm
10020 | 3000K WARM WHITE 10021 | 4000K DAY WHITE 10022 | 6500K WHITE	VT-44030-B	30W	2505	20 pcs		164x29x139mm
10026 | 6500K WHITE	VT-44050-B	50W	4270	20 pcs		183x29x169mm
10348 | 6500K WHITE	VT-44100	100W	8700	8 pcs		254x33x217mm

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.






IP65 RATING

05 YEAR WARRANTY

LED FLOODLIGHTS WHITE BODY WHITE GLASS

- IP65 Rating.
- SMD-Samsung Chip
- 5 Years Warranty
- AC:220-240V,50Hz
- Body Type: Aluminium
- 115° Beam Angle
- CRI >70
- PF >0.9
- 25,000 hr lifespan
- 0-100% in <1sec

SKU	Model	Watts	Lumens	Box Qty	Diagram	Size
10011 | 3000K WARM WHITE 10012 | 4000K DAY WHITE 10013 | 6500K WHITE	VT-44010-W	10W	735	40 pcs		104x21x92mm
10017 | 3000K WARM WHITE 10018 | 4000K DAY WHITE 10019 | 6500K WHITE	VT-44020-W	20W	1620	20 pcs		126.5x28x114mm
10023 | 3000K WARM WHITE 10024 | 4000K DAY WHITE 10025 | 6500K WHITE	VT-44030-W	30W	2505	20 pcs		164x29x139mm

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.





HIGH POWER LED FLOODLIGHTS

IP65 RATING

05 YEAR WARRANTY

- IP65 Rating.
- SMD-Samsung Chip
- 5 Years Warranty
- AC:220-240V,50Hz
- Body Type: Aluminium
- 115° Beam Angle
- CRI >70
- PF >0.9
- 25,000 hr lifespan
- 0-100% in <1sec

SKU	Model	Watts	Lumens	Box Qty	Diagram	Size
10027 | 4000K DAY WHITE 10028 | 6500K WHITE	VT-44200-B	200W	17540	4 pcs		405x36x326mm
10031 | 4000K DAY WHITE 10032 | 6500K WHITE	VT-44300-B	300W	26390	2 pcs		496x49x445mm





HIGH POWER LED FLOODLIGHTS

IP65 RATING

05 YEAR WARRANTY

- IP65 Rating.
- SMD-Samsung Chip
- 5 Years Warranty
- AC:220-240V,50Hz
- Body Type: Aluminium
- 115° Beam Angle
- CRI >70
- PF >0.9
- 25,000 hr lifespan
- 0-100% in <1sec

SKU	Model	Watts	Lumens	Box Qty	Diagram	Size
10029 | 4000K DAY WHITE 10030 | 6500K WHITE	VT-44200-W	200W	17540	4 pcs		405x36x326mm
10033 | 4000K DAY WHITE 10034 | 6500K WHITE	VT-44300-W	300W	26390	2 pcs		496x49x445mm

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.





IP65 RATING

05 YEAR WARRANTY

EFFICIENCY 180 LUMENS/W

HIGH LUMEN EVOLUTION SERIES

- IP65 Rating.
- SMD
- 5 Years Warranty
- AC:220-240V,50Hz
- Die cast Aluminium body
- 100° Beam Angle
- CRI >70
- PF>0.9
- 25,000 hr lifespan
- On/Off Cycle >15000

SKU	Model	Watts	Lumens	Box Qty	Diagram	Size
20450 | 6500K WHITE	VT-30185	30W	4720	10 pcs		165x204.5x46mm
20452 | 6500K WHITE	VT-50185	50W	7870	10 pcs		197.5x241.5x46mm

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.







IP65 RATING

02 YEAR WARRANTY

EFFICIENCY 185 LUMENS/W

HIGH LUMEN EVOLUTION SERIES

- IP65 Rating.
- SMD
- 2 Years Warranty
- AC:220-240V,50Hz
- Body Type: Aluminium
- CRI >70
- PF>0.9
- 25,000 hr lifespan
- 0-100% in <1sec

SKU	Model	Watts	Lumens	Box Qty	Diagram	Size
9255 | 4000K DAY WHITE 9891 | 6500K WHITE	VT-4435	30W	5550	10 pcs		164.5x34x153mm
9892 | 4000K DAY WHITE 9893 | 6500K WHITE	VT-4456	50W	9250	10 pcs		183.5x34x169mm
9894 | 4000K DAY WHITE 9895 | 6500K WHITE	VT-44105	100W	18500	4 pcs		253.5x40x242.5mm
9896 | 4000K DAY WHITE 9897 | 6500K WHITE	VT-44205	200W	37000	2 pcs		402.5x44x349.5mm

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.






IP65 RATING

05 YEAR WARRANTY

EFFICIENCY 160 LUMENS/W

HIGH LUMEN SLIMLINE PRO SERIES

- IP65 Rating.
- SMD-Samsung Chip
- 5 Years Warranty
- AC:220-240V,50Hz
- Die cast Aluminium body
- 100° Beam Angle
- CRI >70
- PF>0.9
- 25,000 hr lifespan
- On/Off Cycle >15000

SKU	Model	Watts	Lumens	Box Qty	Diagram	Size
20403 | 6500K WHITE	VT-32	30W	4100	10 pcs		165x204.5x46mm
20405 | 6500K WHITE	VT-52	50W	6850	10 pcs		197.5x241.5x46mm
20409 | 6500K WHITE	VT-162	150W	20500	2 pcs		318.5x390x55mm

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.








IP65 RATING

02 YEAR WARRANTY

EFFICIENCY 160 LUMENS/W

HIGH LUMEN EVOLUTION SERIES

- IP65 Rating.
- SMD
- 2 Years Warranty
- AC:220-240V,50Hz
- Body Type: Aluminium
- CRI >70
- PF>0.9
- 25,000 hr lifespan
- 0-100% in <1sec

SKU	Model	Watts	Lumens	Box Qty	Diagram	Size
10353 | 4000K DAY WHITE	VT-44031	30W	4800	10 pcs		164.5x34x153mm
10354 | 4000K DAY WHITE	VT-44051	50W	8000	10 pcs		183.5x34x169mm
10355 | 4000K DAY WHITE	VT-44106	100W	16000	4 pcs		253.5x40x242.5mm
10362 | 4000K DAY WHITE	VT-44160	150W	24000	4 pcs		328.5x43x295mm
10363 | 4000K DAY WHITE 10365 | 6500K WHITE	VT-44206	200W	32000	2 pcs		402.5x44x349.5mm

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.



IP65 RATING






05 YEAR WARRANTY

AUTOMATIC SENSOR
OFF
ON
≤15Lux

- The floodlights work automatically, according to the level of surrounding light.
- The floodlight will automatically turn on at light levels below 140lux. At light levels above 140lux, the floodlight will turn off.
- There is no need to manually switch the light on or off.
- Floodlights with automatic light sensors do not react to motion.

LED FLOODLIGHTS WITH LIGHT SENSOR

- Die cast Aluminium body
- 100° beam angle
- 25,000 hrs lifespan
- >15000 On/Off Cycles
- CRI: >80
- PF: >0.9
- AC:220-240V,50Hz
- IP65 Rating

SKU	Model	Watts	Lumens	Box Qty	Diagram	Size
20169 | 3000K WARM WHITE 20170 | 4000K DAY WHITE 20171 | 6500K WHITE	VT-37	30W	3000	20 pcs		165x46x204.5mm
20172 | 3000K WARM WHITE 20173 | 4000K DAY WHITE 20174 | 6500K WHITE	VT-57	50W	5000	10 pcs		197.5x46x241.5mm
20175 | 3000K WARM WHITE 20176 | 4000K DAY WHITE 20177 | 6500K WHITE	VT-117	100W	10000	4 pcs		247.5x49.5x299mm
20178 | 3000K WARM WHITE 20179 | 4000K DAY WHITE 20180 | 6500K WHITE	VT-167	150W	15000	2 pcs		318.5x55x390mm
20181 | 3000K WARM WHITE 20182 | 4000K DAY WHITE 20183 | 6500K WHITE	VT-272	200W	20000	2 pcs		371x57x458.5mm

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.



IP65 RATING





05 YEAR WARRANTY

DIY DO IT YOURSELF

- Instant start in 1 second
- Operation in outside temperatures (-20 to+40° C)
- Protection rating IP65
- Only connect with waterproof cable.

LED FLOODLIGHTS - DIRECT CONNECTION

- Die cast Aluminium body
- 100° beam angle
- 25,000 hrs lifespan
- >15000 On/Off Cycles
- CRI: >80
- PF: >0.9
- AC:220-240V,50Hz
- IP65 Rating

SKU	Model	Watts	Lumens	Box Qty	Diagram	Size
20304 | 3000K WARM WHITE 20305 | 4000K DAY WHITE 20306 | 6500K WHITE	VT-118	10W	735	20 pcs		133x55x88mm
20307 | 3000K WARM WHITE 20308 | 4000K DAY WHITE 20309 | 6500K WHITE	VT-128	20W	1510	20 pcs		157x56x101mm
20310 | 3000K WARM WHITE 20311 | 4000K DAY WHITE 20312 | 6500K WHITE	VT-138	30W	2340	10 pcs		177x56x117mm
20313 | 3000K WARM WHITE 20314 | 4000K DAY WHITE 20315 | 6500K WHITE	VT-158	50W	4000	10 pcs		195x57x152mm

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.



IP65 RATING





05 YEAR WARRANTY

DIY DO IT YOURSELF

- Instant start in 1second
- Operation in outside temperaturess (-20 to +40° C)
- Manual override function
- When the lock sensor function, avoid long time lighting in extreme weather.

LED FLOODLIGHTS - DIRECT CONNECTION WITH PIR SENSOR

- Die cast Aluminium body
- 100° beam angle
- 25,000 hrs lifespan
- >15000 On/Off Cycles
- 140°±20° Detection Range
- CRI: >80
- PF: >0.9
- AC:220-240V,50Hz
- IP65 Rating
- 3-10m Detection Distance

SKU	Model	Watts	Lumens	Box Qty	Diagram	Size
20256 | 3000K WARM WHITE 20257 | 4000K DAY WHITE 20258 | 6500K WHITE	VT-118S-B	10W	735	20 pcs		133x60x113mm
20259 | 3000K WARM WHITE 20260 | 4000K DAY WHITE 20261 | 6500K WHITE	VT-128S-B	20W	1510	20 pcs		157x60x128mm
20262 | 3000K WARM WHITE 20264 | 6500K WHITE	VT-138S-B	30W	2340	10 pcs		177x60x143mm
20266 | 4000K DAY WHITE	VT-158S-B	50W	4000	10 pcs		195x60x178mm

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.



IP65 RATING





05 YEAR WARRANTY

DIY DO IT YOURSELF

- Instant start in 1second
- Operation in outside temperaturess (-20 to +40° C)
- Manual override function
- When the lock sensor function, avoid long time lighting in extreme weather.

LED FLOODLIGHTS - DIRECT CONNECTION WITH PIR SENSOR

- Die cast Aluminium body
- 100° beam angle
- 25,000 hrs lifespan
- >15000 On/Off Cycles
- 140°±20° Detection Range
- CRI: >80
- PF: >0.9
- AC:220-240V,50Hz
- IP65 Rating
- 3-10m Detection Distance

SKU	Model	Watts	Lumens	Box Qty	Diagram	Size
20269 | 4000K DAY WHITE 20270 | 6500K WHITE	VT-118S-W	10W	735	20 pcs		133x60x113mm
20273 | 6500K WHITE	VT-128S-W	20W	1510	20 pcs		157x60x128mm
20276 | 6500K WHITE	VT-138S-W	30W	2340	10 pcs		177x60x143mm
20279 | 6500K WHITE	VT-158S-W	50W	4000	10 pcs		195x60x178mm

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.



IP65 RATING

05 YEAR WARRANTY





PIR MOTION SENSOR

1 METER WIRE

- Instant start in 1second
- Operation in outside temperaturess (-20 to +40° C)
- Manual override function
- When the lock sensor function, avoid long time lighting in extreme weather.
- Extra-long 1 meter cable included for easy installation.

LED FLOODLIGHTS WITH PIR SENSOR

- Die cast Aluminium body
- 100° beam angle
- 25,000 hrs lifespan
- >15000 On/Off Cycles
- 140°±20° Detection Range
- CRI: >80
- PF: >0.9
- AC:220-240V,50Hz
- IP65 Rating
- 3-10m Detection Distance

SKU	Model	Watts	Lumens	Box Qty	Diagram	Size
20280 | 3000K WARM WHITE 20281 | 4000K DAY WHITE 20282 | 6500K WHITE	VT-118S-1-B	10W	735	20 pcs		133x60x113mm
20283 | 3000K WARM WHITE 20284 | 4000K DAY WHITE 20285 | 6500K WHITE	VT-128S-1-B	20W	1510	20 pcs		157x60x128mm
20286 | 3000K WARM WHITE 20287 | 4000K DAY WHITE 20288 | 6500K WHITE	VT-138S-1-B	30W	2340	10 pcs		177x60x143mm
20289 | 3000K WARM WHITE 20290 | 4000K DAY WHITE 20291 | 6500K WHITE	VT-158S-1-B	50W	4000	10 pcs		195x60x178mm

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.



IP65 RATING

05 YEAR WARRANTY





PIR MOTION SENSOR

1 METER WIRE

- Instant start in 1second
- Operation in outside temperaturess (-20 to +40° C)
- Manual override function
- When the lock sensor function, avoid long time lighting in extreme weather.
- Extra-long 1 meter cable included for easy installation.

LED FLOODLIGHTS WITH PIR SENSOR

- Die cast Aluminium body
- 100° beam angle
- 25,000 hrs lifespan
- >15000 On/Off Cycles
- 140°±20° Detection Range
- CRI: >80
- PF: >0.9
- AC:220-240V,50Hz
- IP65 Rating
- 3-10m Detection Distance

SKU	Model	Watts	Lumens	Box Qty	Diagram	Size
20292 | 3000K WARM WHITE 20293 | 4000K DAY WHITE 20294 | 6500K WHITE	VT-118S-1-W	10W	735	20 pcs		133x60x113mm
20295 | 3000K WARM WHITE 20296 | 4000K DAY WHITE 20297 | 6500K WHITE	VT-128S-1-W	20W	1510	20 pcs		157x60x128mm
20298 | 3000K WARM WHITE 20299 | 4000K DAY WHITE 20300 | 6500K WHITE	VT-138S-1-W	30W	2340	10 pcs		177x60x143mm
20301 | 3000K WARM WHITE 20302 | 4000K DAY WHITE 20303 | 6500K WHITE	VT-158S-1-W	50W	4000	10 pcs		195x60x178mm

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.



IP65 RATING





05 YEAR WARRANTY

PIR MOTION SENSOR

Incorporating security features, V-TAC offers a new range of LED floodlights equipped with PIR sensors and Samsung LEDs for even better high-end performance. Can be used as a regular floodlight through the Auto Cut-off function(manual override). Widely used for security lighting in residential, commercial, and industrial areas.

LED FLOODLIGHTS WITH PIR SENSOR

- 30,000 hr lifespan
- 100° Beam Angle
- AC:220-240V,50Hz
- CRI: >80
- PF>0.7 for 10,20w; 0.9 for 30,50w
- On/Off cycle: >15000
- Instant start in <1sec
- Die-cast Aluminium Body
- Detection Angle:120°
- Detection distance:2-8m
- Time delay: MIN12+-3sec MAX6+-2min
- Installation height: 1.8-2.5m

SKU	Model	Watts	Lumens	Wire	Box Qty	Diagram	Size
433 | 3000K WARM WHITE 434 | 4000K DAY WHITE 435 | 6400K WHITE	VT-10-S-W	10W	800	1 meter	20 pcs		114.5x54.86x153.78mm
448 | 3000K WARM WHITE 449 | 4000K DAY WHITE 450 | 6400K WHITE	VT-20-S-W	20W	1600	1 meter	20 pcs		153x55.46x177.75mm
457 | 3000K WARM WHITE 458 | 4000K DAY WHITE 459 | 6400K WHITE	VT-30-S-W	30W	2400	1 meter	20 pcs		178x57.16x197.75mm
466 | 3000K WARM WHITE 468 | 6400K WHITE	VT-50-S-W	50W	4000	1 meter	10 pcs		223x57.06x234.3mm

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.



IP65 RATING




05 YEAR WARRANTY

PIR MOTION SENSOR

Incorporating security features, V-TAC offers a new range of LED floodlights equipped with PIR sensors and Samsung LEDs for even better high-end performance. Can be used as a regular floodlight through the Auto Cut-off function(manual override). Widely used for security lighting in residential, commercial, and industrial areas.

LED FLOODLIGHTS WITH PIR SENSOR

- 30,000 hr lifespan
- 100° Beam Angle
- AC:220-240V,50Hz
- CRI: >80
- PF>0.7 for 10,20w; 0.9 for 30,50w
- On/Off cycle: >15000
- Instant start in <1sec
- Die-cast Aluminium Body
- Detection Angle:120°
- Detection distance:2-8m
- Time delay: MIN12+-3sec MAX6+-2min
- Installation height: 1.8-2.5m

SKU	Model	Watts	Lumens	Wire	Box Qty	Diagram	Size
436 | 3000K WARM WHITE 437 | 4000K DAY WHITE	VT-10-S-B	10W	800	1 meter	20 pcs		114.5x54.86x153.78mm
451 | 3000K WARM WHITE 452 | 4000K DAY WHITE	VT-20-S-B	20W	1600	1 meter	20 pcs		153x55.46x177.75mm
460 | 3000K WARM WHITE	VT-30-S-B	30W	2400	1 meter	20 pcs		178x57.16x197.75mm

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.






IP65 RATING

05 YEAR WARRANTY






V-TAC's PRO Series LED floodlights are equipped with Samsung LEDs for a well-diffused, high-performance outdoor lighting encased in a IP65-rated die-cast aluminium body for durability.
Available in 10-300W in a clean, ivory white finish. Select models come with a one (1) meter wire.

SLIMLINE WHITE BODY

- IP65 Rating.
- SMD-Samsung Chip
- 5 Years Warranty
- AC:220-240V,50Hz
- Die cast Aluminium body
- 100° Beam Angle
- CRI >80
- PF>0.9
- 25,000 hr lifespan
- On/Off Cycle >15000

SKU	Model	Watts	Lumens	Wire	Box Qty	Diagram	Size
444 | 6400K WHITE	VT-20-W	20W	1600	30cm	20 pcs		153x132x27mm
21442 | 3000K WARM WHITE	VT-20-W-N	20W	1510	1 meter	20 pcs		153x132x27mm
21404 | 4000K DAY WHITE	VT-30-W-N	30W	2340	1 meter	10 pcs		178x152x28mm

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SKU	Model	Watts	Lumens	Wire	Box Qty	Diagram	Size
950 | 6400K WHITE	VT-30-1-W	30W	2400	30cm	10 pcs		178x152 x28mm
21410 | 4000K DAY WHITE	VT-50-W-N	50W	4000	30cm	8 pcs		223x188x28mm
21417 | 6500K WHITE	VT-100-W-N	100W	8200	1 meter	4 pcs		291x240x30mm
478 | 3000K WARM WHITE	VT-150-W	150W	12000	1 meter	2 pcs		404x322x52mm
21420 | 4000K DAY WHITE 21421 | 6500K WHITE	VT-200-W-N	200W	16500	1 meter	2 pcs		439x346x48mm

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.







IP65 RATING

05 YEAR WARRANTY





V-TAC's PRO Series LED floodlights are equipped with Samsung LEDs for a well-diffused, high-performance outdoor lighting encased in a IP65-rated die-cast aluminium body for durability. Available in 10-300W in a classic, jet black finish. Select models come with a one (1) meter wire.

SLIMLINE BLACK BODY

- IP65 Rating.
- SMD-Samsung Chip
- 5 Years Warranty
- AC:220-240V,50Hz
- Die cast Aluminium body
- 100° Beam Angle
- CRI >70
- PF>0.9
- 25,000 hr lifespan
- On/Off Cycle >15000

SKU	Model	Watts	Lumens	Wire	Box Qty	Diagram	Size
21947 | 6500K WHITE	VT-10-1-B-N	10W	735	1 meter	20 pcs		115x108x26mm
20012 | 4000K DAY WHITE	VT-20-1-B	20W	1600	1 meter	20 pcs		153x132x27mm
21948 | 6500K WHITE	VT-20-1-B-N	20W	1510	1 meter	20 pcs		153x132x27mm
21407 | 4000K DAY WHITE	VT-50-B-N	50W	4000	1 meter	8 pcs		223x188x28mm

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SKU	Model	Watts	Lumens	Wire	Box Qty	Diagram	Size
2120014 | 4000K DAY WHITE	VT-50-1-B-N	50W	4000	1 meter	8 pcs		223x188x28mm
21476 | 4000K DAY WHITE 21477 | 6500K WHITE	VT-150-B-N	150W	12000	1 meter	2 pcs		327x265x33mm
21418 | 4000K DAY WHITE 21419 | 6500K WHITE	VT-200-B-N	200W	16500	1 meter	2 pcs		439x346x48mm
21422 | 4000K DAY WHITE	VT-300-B-N	300W	24800	1 meter	2 pcs		529x415x55mm

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.








IP65 RATING

05 YEAR WARRANTY

V-TAC's PRO Series LED floodlights are equipped with Samsung LEDs for a well-diffused, high-performance outdoor lighting encased in a die-cast IP65 body for durability. Available in 10W to 300 watts, in a modern, neutral grey finish. Select models come with a one (1) meter wire.

SLIMLINE GREY BODY

- IP65 Rating.
- SMD-Samsung Chip
- 5 Years Warranty
- AC:220-240V,50Hz
- Die cast Aluminium body
- 100° Beam Angle
- CRI >80
- PF>0.9
- 30,000 hr lifespan
- On/Off Cycle >15000

SKU	Model	Watts	Lumens	Wire	Box Qty	Diagram	Size
430 | 3000K WARM WHITE 431 | 4000K DAY WHITE	VT-10-G	10W	800	30cm	20 pcs		115x108x26mm
445 | 3000K WARM WHITE 446 | 4000K DAY WHITE	VT-20-G	20W	1600	30cm	20 pcs		153x132x27mm
454 | 3000K WARM WHITE 455 | 4000K DAY WHITE 456 | 6400K WHITE	VT-30-G	30W	2400	30cm	10 pcs		178x152 x28mm
21464 | 4000K DAY WHITE	VT-50-G-N	50W	4000	1 meter	8 pcs		223x188x28mm
21473 | 4000K DAY WHITE	VT-100-G-N	100W	8200	1 meter	4 pcs		291x240x30mm

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

SOS FLASH

MICRO SOCKET




USB PORT



A strong, reliable, and portable lamp –– V-TAC's new compact and rechargeable LED floodlights can easily be recharged through the micro socket & USB port, making them perfect for home projects, garages, warehouses, car repair shops, parking lots, camping and more.

RECHARGEABLE FLOODLIGHTS

- LED provided by Samsung
- Saves 80% energy
- Function: 100%-50%-SOS
- 3.7V Li-Ion 3600mAh battery
- Rechargeable
- Contains no lead or mercury
- 30,000 hr lifespan

SKU	Model	Watts	Lumens	Wire Type	Box Qty	Diagram	Size
20038 | 4000K DAY WHITE 503 | 6400K WHITE	VT-10-R	10W	700	micro usb cable without SOS Flash	20 pcs		175x125mm
20037 | 4000K DAY WHITE 502 | 6400K WHITE	VT-11-R	10W	700	micro usb cable	20 pcs		175x125mm
20039 | 4000K DAY WHITE 504 | 6400K WHITE	VT-20-R	20W	1400	micro usb cable	20 pcs		175x125mm

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

NEW




05 YEAR WARRANTY

135 LUMEN/W

IP65 RATING

SUPER PRO SERIES-500W

- Sphere 360° Beam Angle
- CRI: >70
- PF: > 0.9
- AC: 220-240V,50Hz
- Material: Die-cast Aluminium
- 25,000 hr lifespan

SKU	Model	Watts	Lumens	Wire	Box Qty	Diagram	Size
23616 | 4000K DAY WHITE 23617 | 6500K WHITE	VT-48501	500W	67500	1 meter	1 pcs		530x65x523mm

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.

05 YEAR WARRANTY

120 LUMEN/W

MEAN WELL Your Reliable Power Partner

IK08 RATING

DIMMABLE

IP66 RATING
















Our heavy-duty IP66 LED Floodlights are perfect for industrial lighting. Never worry about efficiency –– these floodlights are equipped with critically acclaimed LEDs provided by Samsung and excellent MEAN WELL drivers to ensure optimal energy saving and temperature dissipation.

SUPER PRO SERIES-500W

- CRI: >70
- PF: > 0.9
- AC: 100-277V
- Material: Die-cast Aluminium
- 50,000 hr lifespan

SKU	Model	Watts	Lumens	Beam Angle	Box Qty	Diagram	Size
496 | 4000K DAY WHITE	VT-503D	500W	60000	120°	1 pcs		563.8x510x136.75mm
498 | 4000K DAY WHITE	VT-1003D	1000W	120000	120°	1 pcs		965.8x510x136.25mm
499 | 4000K DAY WHITE	VT-1002D	1000W	120000	60°	1 pcs		965.8x510x136.25mm

*Suitable for use up to 10-12 hours daily, constant use of the product will void the warranty.