V-TAC
Meaningful Innovation.

Product Spec Sheet

VT-50-S 50W SMD PIR SENSOR FLOODLIGHT SAMSUNG CHIP 4000K WHITE BODY



FEATURES

- PIR Sensor Floodlight built with adjustable sensor head
- Designed with Manual Override functionality
- IP65 protection - Built with 1 Meter wire.
- Designed with high efficiency LED Samsung Chips
- Built in driver - no external power supply required
- Built Strong and durable with Die Cast Aluminium - Corrosion resistant design
- Suitable for driveways, gardens, patio, building, security lighting etc.

TECHNICAL INFORMATION

Dimmable:	No
Color Temperature:	4000K
Model:	VT-50-S-W
Watts:	50
Lumens:	4000
Input Power:	AC:220-240V, 50Hz
Unit Color:	White
Color for Web:	Day White
Body Type:	Die Cast Aluminium
Dimension:	223x57.06x234.3mm
Operation Temperature:	-20°C to +45°C
Instant Start:	0-100% in <1s
On/Off Cycles:	>15000
Detection Range:	120
Time Delay:	Min: 12sec±3sec/ Max:6min±2min
LED Chip Solution:	9V 100mA
PF:	>0.9
LED Chip Type:	SMD-Samsung Chip
Beam Angle:	100°
Detection Angle:	120
Detection Distance:	2-8m(<24C°)
CRI:	>80
Downward LOR (%):	100
ULR (%):	0
Energy Rating Label:	F (2021)
IP Rating:	IP65
Long Life:	30,000 Hours
Energy Saving:	85 Energy
Wire Length:	1m
Sensor Type:	PIR
IK Rating:	IK05
Samsung:	Yes
EMC Certificate:	Check the certificate
LVD Certificate:	Check the certificate
ROHS Certificate:	Check the certificate

A→G F | IP65 STANDARD | 05 YEAR WARRANTY | SAMSUNG LED Illuminated

LISTING DETAILS

SKU:	467
Model:	VT-50-S-W
EAN:	3800157631235
Commodity Code:	94054210

PACKAGING

Gross Weight (Kgs):	1.072
Unit CBM:	0.0039
Dimension:	223x57.06x234.3mm

MASTER BOX PACKAGING

Box Qty:	8
Qty Per Pallet:	288
Length (Box) mm:	65
Width (Box) mm:	240
Height (Box) mm:	250