



Manufactured in France

1 temperature cabinet

Large size

Premium Pack

Built-in and flush-fitted, 1 temperature cabinet, for ageing of wine

Technical specifications

Capacity 89 bottles maximum*

Temperature - Default setup temperature: 12°C/54°F
- Temperature setting range from 5°C to 20°C / 41-68°F

Design

- 4 doors options: full glass door, stainless steel glass door, technical solid door, technical glass door (reversible integrated glass door with soft close and door stop)
- Lock (except technical door)
- LED screen with backlit capacitive keys
- Amber inner lighting: atmosphere lighting with the light strip and 2 LEDs
- 3 lighting options: permanent, open door, disabled
- Amber screen display

Accessories

- 14 sliding shelves with Mains du Sommelier (possible adjustment of the position of the MDS, on the front) + grid
- Light oak and black glossy front
- 6 removable bottles identifiers per sliding shelf
- 1 erasable felt-tip marker
- 1 microfiber cloth
- 1 keyring

Equipment

- Charcoal filter (with counter)
- Humidity cassette with clay ball
- Low-emissivity glass and argon gas between the 2 glasses (in glass door or full glass finish)
- 4 adjustable feet
- Condensate drip tray at the back

Regulation

- Electronic regulation
- Display of the real temperature inside the cabinet
- Possible humidity display
- Display standby mode, possible
- Visual and audible alarms: temperature fault, sensor fault and open door
- Visual alarms: humidity fault and carbon filter change
- Automatic defrost
- Frost protection thermostat (double protection)

Technologies

- Cold production:** Ventilated
- Cords:** CE/US/UK/JA/AU/CH/CA/CN
- Hot production:** Heating element
- Hot release:** Automatic/ threshold: adjustable
- Inner material:** Stucco aluminium
- Exterior coating material:** HDF (High Density Fiber) melamine-faced panels
- Insulation type:** PU Foam (59mm)

Equipment
Standard shelf



Sliding shelf
ACV5B
6 bottles



Sliding shelf
ACV5W
6 bottles

Equipment
Optional shelves



Sliding wine service area
ACV6R/B
11 bottles



Sliding wine service area
ACV6R/W
11 bottles



Storage shelf
A3HB
22 bottles



Storage shelf
A3HW
22 bottles



Half shelf
ACV6-CB/A
5 bottles

*Traditional Bordeaux format



Manufactured in France

1 temperature cabinet

Large size

Access Pack

Built-in and flush-fitted, 1 temperature cabinet, for ageing of wine

Technical specifications

Equipment
Standard shelves



Sliding shelf
ACMSB
6 bottles



Sliding shelf
AQMSW
6 bottles



Storage shelf
A2HB
22 bottles



Storage shelf
A2HW
22 bottles

Equipment
Optional shelves



Sliding wine service area
ACMSBVB
11 bottles



Sliding wine service area
ACMSBVI
11 bottles



Half shelf
AQMSBEM
5 bottles

Capacity 89 bottles maximum*

Temperature - Default setup temperature: 12°C/54°F
- Temperature setting range from 5°C to 20°C / 41-68°F

Design

- 4 doors options: full glass door, stainless steel glass door, technical solid door, technical glass door (reversible integrated glass door with soft close and door stop)
- Lock (except technical door)
- LED screen with backlit capacitive keys
- Amber inner lighting: atmosphere lighting with the light strip and 2 LEDs
- 3 lighting options: permanent, open door, disabled
- Amber screen display

Accessories

- 3 sliding shelves with Mains du Sommelier (possible adjustment of the position of the MDS, on the front)
- 3 storage shelves (+grid)
- Light oak and black glossy front
- 6 removable bottles identifiers per sliding shelf
- 1 erasable felt-tip marker
- 1 microfiber cloth
- 1 keyring

Equipment

- Charcoal filter (with counter)
- Humidity cassette with clay ball
- Low-emissivity glass and argon gas between the 2 glasses (in glass door or full glass finish)
- 4 adjustable feet
- Condensate drip tray at the back

Regulation

- Electronic regulation
- Display of the real temperature inside the cabinet
- Possible humidity display
- Display standby mode, possible
- Visual and audible alarms: temperature fault, sensor fault and open door
- Visual alarms: humidity fault and carbon filter change
- Automatic defrost
- Frost protection thermostat (double protection)

Technologies

Cold production:	Ventilated
Cords:	CE/US/UK/JA/AU/CH/C6/CN
Hot production:	Heating element
Hot release:	Automatic/ threshold: adjustable
Inner material:	Stucco aluminium
Exterior coating material:	HDF (High Density Fiber) melamine-faced panels
Insulation type:	PU Foam (59mm)

*Traditional Bordeaux format