EUROCAVE

V-INSP-S

Inspiration

Manufactured in France | 1 temperature cabinet | Small size | Access Pack

Built-in and flush-fitted, 1 temperature cabinet, for ageing of wine



5 YEAR WARRANTY

Equipment
Standard shelves



Sliding shelf
ADMSBB
6 bottles



Sliding shelf
ADMSW
6 bottles



Storage shelf
AXHB
22 bottles



Storage shelf
AXHW
22 bottles

Equipment
Optional shelves



Sliding wine service area
ACMSBRVB
11 bottles



Sliding wine service area
ACMSBRVW
11 bottles



Half shelf
ADMSHDEMI
5 bottles

Technical specifications

Capacity	30 bottles maximum*	
Temperature	· Default setup temperature: 12°C/54°F · Temperature setting range from 5°C to 20°C / 41-68°F	
Design	· 4 doors options: full glass door, stainless steel glass door, technical solid door, technical glass door (reversible integrated glass door with soft close and door stop) · Lock (except technical door) · LED screen with backlit capacitive keys	· Amber inner lighting: atmosphere lighting with the light strip and 2 LEDs · 3 lighting options: permanent, open door, disabled · Amber screen display
Accessories	· 1 sliding shelf with Mains du Sommelier (possible adjustment of the position of the MDS, on the front) · 1 storage shelf (+grid) · Light oak and black glossy front	· 6 removable bottles identifiers per sliding shelf · 1 erasable felt-tip marker · 1 microfiber cloth · 1 key ring
Equipement	· Charcoal filter (with counter) · Humidity cassette with clay ball	· Low-emissivity glass and argon gas between the 2 glasses (in glass door or full glass finish) · 4 adjustable feet · Condensate drip tray at the back
Regulation	· Electronic regulation · Display of the real temperature inside the cabinet · Possible humidity display · Display standby mode, possible	· Visual and audible alarms: temperature fault, sensor fault and open door · Visual alarms : humidity fault and carbon filter change · Automatic defrost · Frost protection thermostat (double protection)
Technologies	**Cold production:**	Static/ Compressor R600a
	Cords:	CE/US/UK/JA/AU/CH/C6/CN
	Hot production:	Heating element
	Hot release:	Automatic/ threshold : adjustable
	Inner material:	Stucco aluminium
	Exterior coating material:	HDF (High Density Fiber) melamine-faced panels
	Insulation type:	PU Foam (59mm)

*Traditional Bordeaux format

EUROCAVE

V-INSP-S

Inspiration

Manufactured in France | 1 temperature cabinet | Small size | Premium Pack

Built-in and flush-fitted, 1 temperature cabinet, for ageing of wine



5 YEAR WARRANTY

Equipment
Standard shelf



Sliding shelf
ACMSB
6 bottles



Sliding shelf
ACMSW
6 bottles

Equipment
Optional shelves



Sliding wine service area
ACMSBR/B
11 bottles



Sliding wine service area
ACMSBR/W
11 bottles



Storage shelf
AXIHB
22 bottles



Storage shelf
AXIHW
22 bottles



Half shelf
ACMSI-DEMI
5 bottles

Technical specifications

Capacity	29 bottles maximum*	
Temperature	·Default setup temperature: 12°C/54°C ·Temperature setting range from 5°C to 20°C / 41-68°F	
Design	·4 doors options: full glass door, stainless steel glass door, technical solid door, technical glass door (reversible integrated glass door with soft close and door stop) ·Lock (except technical door) ·LED screen with backlit capacitive keys	·Amber inner lighting: atmosphere lighting with the light strip and 2 LEDs ·3 lighting options: permanent, open door, disabled ·Amber screen display
Accessories	·4 sliding shelves with Mains du Sommelier (possible adjustment of the position of the MDS, on the front) + grid ·Light oak and black glossy front	·6 removable bottles identifiers per sliding shelf ·1 erasable felt-tip marker ·1 microfiber cloth ·1 key ring
Equipement	·Charcoal filter (with counter) ·Humidity cassette with clay ball	·Low-emissivity glass and argon gas between the 2 glasses (in glass door or full glass finish) ·4 adjustable feet ·Condensate drip tray at the back
Regulation	·Electronic regulation ·Display of the real temperature inside the cabinet ·Possible humidity display ·Display standby mode, possible	·Visual and audible alarms: temperature fault, sensor fault and open door ·Visual alarms: humidity fault and carbon filter change ·Automatic defrost ·Frost protection thermostat (double protection)
Technologies	**Cold production:**	Static/Compressor R600a
	Cords:	CE/US/UK/JA/AU/CH/C6/CN
	Hot production:	Heating element
	Hot release:	Automatic/ threshold : adjustable
	Inner material:	Stucco aluminium
	Exterior coating material:	HDF (High Density Fiber) melamine-faced panels
	Insulation type:	PU Foam (59mm)

*Traditional Bordeaux format