

BELLEVE

COLLECTION

PORCELÁNICO · PORCELAIN



COLORES / COLOURS									
									
IVORY		STONE		WHITE		GREY		GRAPHITE	
FORMATO / SIZE						ACABADO / FINISHED		GRUPO / GROUP	
120X120 cm. RECT 47"X47" RECT		60X120 cm. RECT 24"X47" RECT		75X75 cm. RECT 30"X30" RECT		60X60 cm. RECT 24"X24" RECT		30X60 cm. 12"X24"	
						45x45 cm. 18"X18"		Mate/Matt INOUT	
								Bla	

UNE-EN 14411:2016

DESCRIPCIÓN DEL TEST TEST DESCRIPTION		NORMA STANDARD	VALOR DEL TEST TEST VALUE	RESULTADO RESULT
	ABSORCIÓN DE AGUA / WATER ABSORPTION	UNE-EN-ISO 10545-3	Ev ≤ 0,5%	Cumple / Complies
	FUERZA DE ROTURA / BREAKING STRENGTH	UNE-EN-ISO 10545-4	≥ 1300 N	Cumple / Complies
	RESISTENCIA A LA FLEXIÓN / MODULUS OF RUPTURE	UNE-EN-ISO 10545-4	≥ 35 N/mm2	Cumple / Complies
	ABRASIÓN SUPERFICIAL / SURFACE ABRASION	IVORY STONE WHITE GREY GRAPHITE UNE-EN-ISO 10545-7	Valor declarado/ Declared value	Clase 3 / Class 3 Clase 2 / Class 2 Clase 3 / Class 3 Clase 3 / Class 3 Clase 2 / Class 2
	RESISTENCIA AL CUARTEO / CRAZING RESISTANCE	UNE-EN-ISO 10545-11	Requerido / Requested	Cumple / Complies
	RESISTENCIA A LA HELADA / FROST RESISTANCE	UNE-EN-ISO 10545-12	Requerido / Requested	Cumple / Complies
	RESISTENCIA QUÍMICA / CHEMICAL RESISTANCE	PRODUCTOS DOMÉSTICOS Y ADITIVOS PISCINAS / HOUSEHOLD CHEMICALS AND SWIMMING POOL SALTS UNE-EN-ISO 10545-13	Mínimo clase B / Minimum class B	Cumple / Complies
	RESISTENCIA QUÍMICA / CHEMICAL RESISTANCE	ÁCIDOS A BAJA CONCENTRACIÓN / LOW CONCENTRATION OF ACIDS UNE-EN-ISO 10545-13	Valor declarado/ Declared value	Mínimo clase LB / Minimum class LB
	RESISTENCIA QUÍMICA / CHEMICAL RESISTANCE	BASES A BAJA CONCENTRACIÓN/ LOW CONCENTRATION OF ALKALIS UNE-EN-ISO 10545-13	Valor declarado/ Declared value	Mínimo clase LB / Minimum class LB
	RESISTENCIA A LAS MANCHAS / RESISTANCE TO STAINS	UNE-EN-ISO 10545-14	Mínimo clase 3 / Minimum class 3	Cumple / Complies
	RESISTENCIA AL DESLIZAMIENTO / SLIP RESISTANCE	UNE-41901 EX Péndulo / Pendulum		Clase 3 / Class 3
		BS 7976-2:2002 +A1:2013 Resistencia al deslizamiento (Péndulo): Método operativo (PTV) / Slip resistance (Pendulum): Pendulum test value (PTV)		+36
		ANSI A137. 1: 2017. 9.6 Coeficiente de fricción dinámico (D.C.O.F.) / Dynamic coefficient of friction (D.C.O.F.)		>0.63
		DIN 51130:2014-5 Ángulo crítico deslizamiento (Rampa) / Critical angle of slip (Inclined platform)		≥R10
		DIN 51097 Ángulo crítico deslizamiento zonas húmedas de andar descalzo / Critical angle of slip wet-loaded barefoot areas		C
	RESISTENCIA AL RAYADO / HARDNESS (MOHS)	EN-101	Valor declarado/ Declared value	Mínimo 3 / Minimum 3